

Amendments to the Abstract

Please amend the abstract beginning at page 43 and ending at page 44 as follows:

A method of manufacturing an ink jet head, which includes a discharge port for discharging an ink droplet, an ink flow path communicated with the discharge port, and an energy generating element for discharging the ink droplet from the discharge port, ~~the method for manufacturing an ink jet head~~ includes ~~a process of forming~~ providing a photodegradable ~~positive type resist resin~~ layer on a substrate having the energy generating element, ~~a process of forming a structure which becomes the ink flow path by exposing and developing the photodegradable positive type resist resin layer, a process of coating the substrate having the structure which becomes the ink flow path with a negative type resist photosensitive resin layer, a process of forming the ink discharge port in the negative type resist photosensitive resin layer, and a process of forming the ink flow path communicated with the discharge port by removing the structure which becomes the ink flow path[[,]].~~ The wherein the photodegradable positive type resist resin layer includes an a binary acrylic copolymer composition, the acrylic copolymer composition containing at least which contains a unit obtained from (meta) acrylic ester as a main content, ~~the acrylic copolymer composition component and further containing contains~~ a unit obtained from (meta) acrylic acid, ~~the acrylic copolymer~~ . The composition contains the (meta) acrylic acid unit at a proportion of 5 to 30 weight%, and a weight average molecular weight of the acrylic copolymer composition ranges from 50000 to 300000.